

Ref. : VOC424116-00.pas

Rev. : B

Date : 24/03/09

Page : 1/1

RESILIENT SEAT GATE VALVE

VOC424116-00



ROBINETTERIE INDUSTRIELLE ET ACCESSOIRES
INDUSTRIAL VALVES AND ACCESSORIES

APPLICATION

General use : Water supply, fire protection, irrigation, water treatment.

GENERAL CHARACTERISTICS

Range : DN300.
Non rising stem.
Clockwise to close or anti clockwise to close.
No zone of retention.
Low head losses.

CONSTRUCTION

9	1	Hand wheel	Ductile iron
8	1	Gasket	EPDM
7	1	Top nut	Brass
6	1	Ring	Brass
5	1	Bonnet	Ductile iron
4	1	Stem	Stainless steel
3	1	Nut	Brass
2	1	Wedge	EPDM coated ductile iron
1	1	Body	Ductile iron
Pos.	Qty.	Description	Material



DIMENSIONS

DN		L	H	Ø C	Ø D	Ø K	Ø G	f	B	n x d	□ S	Poids (kg)
mm	inch					PN16	PN16			PN16		
300	12"	270	704	400	460	410	378	4	29	12 x 26	24	148

WORKING CONDITIONS

Maximum working pressure : 16 bar.
Maximum temperature : +130°C

STANDARDS

Face to face according to EN558-1 serie 14 and DIN 3202 / F4 Short pattern.
Connection according to standard EN 1092-2 ISO PN10 and ISO PN16.

